


rectifier diodes < 100 A

diodes de redressement < 100 A




Types	I_O (A)	V_{RRM} (V)	I_{FSM} 10 ms (A)	V_F (V)	I_F max (A)	I_R @ V_{RRM} max (μ A)	T_{amb} (°C)	Case
-------	--------------	------------------	---------------------------	--------------	---------------------	---	-------------------	------

200 mA / $T_{amb} = 25^\circ\text{C}$ $T_j = 150^\circ\text{C}$

M12-FR 34 M 22 M 42 M 62 M 82 M 102	0,2	100 200 400 600 800 1000	3	1	0,2	150	125	 <p>DO 7 glass - verre (CB-26)</p>
--	-----	---	---	---	-----	-----	-----	---


400 mA / $T_{amb} = 25^\circ\text{C}$ $T_j = 150^\circ\text{C}$

M 14 Δ 1N 645 1N 646 Δ 1N 647 1N 648 Δ 1N 649	0,4	100 225 300 400 500 600	3	1	0,4	0,5 0,2 0,2 0,2 0,2 0,2	25	 <p>DO 29 glass - verre (CB-126)</p>
---	-----	--	---	---	-----	--	----	---


1 A / $T_{amb} = 50^\circ\text{C}$ $T_j = 175^\circ\text{C}$

1N 4383 1N 4384 1N 4385 1N 4585 1N 4586	1	200 400 600 800 1000	50	1	1	250	150	 <p>F 126 plastic - plastique (CB-210)</p>
---	---	----------------------------------	----	---	---	-----	-----	---


1 A / $T_{amb} = 25^\circ\text{C}$ $T_j = 150^\circ\text{C}$

E 11 E 21 E 41 E 61 E 81 E 101	1	100 200 400 600 800 1000	30	1,2	1	200	125	 <p>F 126 plastic - plastique (CB-210)</p>
---	---	---	----	-----	---	-----	-----	---

1 A / $T_{amb} = 75^\circ\text{C}$ $T_j = 150^\circ\text{C}$

Δ 1N 4001 Δ 1N 4002 Δ 1N 4003 Δ 1N 4004 Δ 1N 4005 Δ 1N 4006 Δ 1N 4007 P 511 P 513	1	50 100 200 400 600 800 1000 1300 1600	50	1,1	1	50	100	 <p>F 126 plastic - plastique (CB-210)</p>
--	---	---	----	-----	---	----	-----	---

1 A / $T_{amb} = 70^\circ\text{C}$ $T_j = 150^\circ\text{C}$

BYW 27-50 BYW 27-100 BYW 27-200 BYW 27-400 BYW 27-600 BYW 27-800 BYW 27-1000	1	50 100 200 400 600 800 1000	50	1	1	0,2	25	 <p>F 126 plastic - plastique (CB-210)</p>
--	---	---	----	---	---	-----	----	---

Δ : Devices under CCQ/CCT
Dispositifs soumis au CCQ/CCT