

TRANSISTORS

DEVICE TYPE NO.	POLARITY	P <sub>d</sub> @ T <sub>c</sub> =25°C		MAXIMUM RATINGS				ELECTRICAL CHARACTERISTICS				CASE
		WATTS	I <sub>c</sub> AMPS	BV <sub>CB0</sub>	BV <sub>CE</sub>	BV <sub>EB0</sub>	h <sub>FE</sub> MIN.	I <sub>c</sub> AMPS	V <sub>CE</sub>	f MHZ *KHZ		
2N2845	NPN	.360	.500	60	30	5	30	.150	10	350	T018	
2N2846	NPN	.800	.500	60	30	5	30	.150	10	350	T039	
2N2847	NPN	.360	.500	60	30	5	40	.150	10	250	T018	
2N2848	NPN	.800	.500	60	30	5	40	.150	10	250	T039	
2N2850-1	NPN	.850	3.00	100	80	5	40	1.00	1	30	T039	
2N2851-1	NPN	.850	3.00	100	80	5	40	1.00	1	30	T039	
2N2852-1	NPN	.850	3.00	100	80	5	20	1.00	1	30	T039	
2N2853-1	NPN	.850	3.00	60	40	5	40	1.00	1	30	T039	
2N2854-1	NPN	.850	3.00	60	40	5	100	1.00	1	30	T039	
2N2855-1	NPN	.850	3.00	60	40	5	40	1.00	1	30	T039	
2N2856-1	NPN	.850	3.00	60	40	5	20	1.00	1	30	T039	
2N2863	NPN	.800	1.00	60	25	5	20	.010	15	100	T039	
2N2864	NPN	.800	1.00	60	25	5	12	.010	15	160	T039	
2N2865	NPN	.200	.050	25	13	3	20	.004	10	600	T072	
2N2868	NPN	.800	1.00	60	40	7	30	.010	10	50	T039	
2N2883	NPN	.800	.300	40	20	4	20	1.00	10	400	T039	
2N2884	NPN	.800	.300	40	20	4	20	1.00	10	400	T039	
2N2890	NPN	.800	3.00	100	80	5	30	.050	10	50	T039	
2N2894A	PNP	.360	.200	12	12	4.5	40	.030	.5	800	T018	
2N2904	PNP	.600	.600	60	40	5	25	.001	10	200	T039	
2N2904A	PNP	.600	.600	60	60	5	40	.001	10	200	T039	
2N2405	PNP	.600	.600	60	40	5	50	.001	10	200	T039	
2N2405A	PNP	.600	.600	60	60	5	100	.001	10	200	T039	
2N2406	PNP	.400	.600	60	40	5	25	.001	10	200	T018	
2N2406A	PNP	.400	.600	60	60	5	40	.001	10	200	T018	
2N2407	PNP	.400	.600	60	40	5	30	.001	10	200	T018	
2N2907A	PNP	.400	.600	60	60	5	100	.001	10	200	T018	
2N2927	PNP	.800	.500	25	25	4	25	.010	10	100	T039	
2N2958	NPN	.600	.600	60	20	5	40	.150	10	250	T039	
2N2959	NPN	.600	.600	60	20	5	100	.150	10	250	T039	
2N2986	NPN	1.00	3.00	185	120	8	40	1.00	5	60	T039	
2N2987	NPN	1.00	1.00	95	80	7	25	2.00	5	30	T039	
2N2988	NPN	1.00	1.00	155	100	7	25	.200	5	30	T039	
2N2989	NPN	1.00	1.00	95	80	7	60	.200	5	30	T039	
2N2990	NPN	1.00	1.00	155	100	7	60	.200	5	30	T039	
2N2991	NPN	2.00	1.00	95	80	7	24	.200	5	30	T039	
2N3019	NPN	.800	1.00	140	80	7	100	.150	10	100	T039	
2N3020	NPN	.800	1.00	140	80	7	40	.150	10	80	T039	
2N3036	NPN	.800	1.20	120	80	7	40	.010	10	50	T039	
2N3053	NPN	5.00	.700	60	40	5	50	.150	10	100	T039	
2N3054	NPN	25.0	4.00	90	60	7	25	.500	4	3	T066	
2N3055	NPN	115	15.0	100	70	7	20	4.00	4	2.5	T03	
2N3073	PNP	.360	.500	60	60	4	25	.010	10	130	T018	
2N3081	PNP	.600	.600	70	50	6	30	.150	10	150	T039	
2N3107	NPN	.800	1.00	100	60	7	60	.001	10	70	T039	
2N3108	NPN	.800	1.00	100	60	7	20	.001	10	60	T039	
2N3109	NPN	.800	1.00	80	40	7	60	.001	10	70	T039	
2N3110	NPN	.800	1.00	80	40	7	20	.001	10	60	T039	
2N3114	NPN	.800	.200	150	150	5	25	.001	5	40	T039	
2N3224	PNP	.700	1.00	100	100	6	20	.001	5	60	T039	
2N3225	PNP	.700	1.00	100	100	6	40	.001	5	80	T039	
2N3226	NPN	75.0	5.00	35	35	6	20	2.00	3	*30	T03	
2N3237	NPN	200	20.0	90	75	5	12	10.0	8	1	T03	
2N3240	NPN	150	15.0	160	160	8	8.5	10.0	10	2	T03	
2N3306	PNP	.600	.100	50	40	6	70	.001	5	20	T039	
2N3307	PNP	.300	.050	40	35	3	40	.002	10	300	T018	
2N3308	PNP	.300	.050	30	25	3	25	.002	10	300	T018	
2N3326	NPN	.800	.800	60	45	5	35	.010	10	250	T039	
2N3337	NPN	.300	.050	40	40	4	30	.004	10	400	T072	
2N3338	NPN	.300	.050	40	40	4	30	.004	10	400	T072	
2N3339	NPN	.300	.050	40	40	4	30	.004	10	400	T072	

