


NTC Thermistors, Surface Mount Chip



FEATURES

- Solderable terminations
- Wraparound terminations
- Allows design flexibility for use with hybrid circuitry
- High-density monolithic construction

NTHS PRODUCT R ₂₅ °C VALUE RANGE BY CURVE AVAILABILITY						
CURVE	NTHS-0402	NTHS-0603	NTHS-0805	NTHS-1206	NTHS-1012	% TOLERANCE AVAILABILITY
3	N/A	1000 - 2000	1000 - 2000	1000 - 2000	500 - 700	5 %, 10 %
6	4.7K - 5.0K	2K - 3.5K	1.5K - 2.8K	1.5K - 3.5K	1000 - 2000	5 %, 10 %
2	10K - 12K	6.8K - 12K	4.7K - 10K	4.7K - 10K	1.3K - 4.3K	3 %, 5 %, 10 %
10	18K - 25K	10K - 20K	6K - 12K	10K - 20K	4.5K - 7K	3 %, 5 %, 10 %
11	30K - 34K	22K - 32K	12K - 30K	20K - 33K	9K - 13K	3 %, 5 %, 10 %
5	47K - 50K	32K - 50K	35K - 50K	30K - 44K	15K - 20K	3 %, 5 %, 10 %
1	68K - 100K	32K - 100K	33K - 100K	32K - 70K	10K - 30K	1 % to 10 %
17	250K	150K - 200K	100K - 200K	100K - 200K	30K - 93K	3 %, 5 %, 10 %
4	350K	200K - 220K	200K - 220K	200K - 330K	93K - 140K	3 %, 5 %, 10 %

GLOBAL PART NUMBER INFORMATION																																					
New Global Part Numbering: NTHS1206N02N1002JR (preferred part numbering format)																																					
<div style="display: flex; justify-content: space-around; font-weight: bold; font-size: 1.2em;"> N T H S 1 2 0 6 N 0 2 N 1 0 0 2 J R </div>																																					
<table border="1"> <tr><th>GLOBAL MODEL</th></tr> <tr><td>NTHS0402</td></tr> <tr><td>NTHS0603</td></tr> <tr><td>NTHS0805</td></tr> <tr><td>NTHS1206</td></tr> <tr><td>NTHS1012</td></tr> </table>	GLOBAL MODEL	NTHS0402	NTHS0603	NTHS0805	NTHS1206	NTHS1012	<table border="1"> <tr><th>CONDUCTOR TYPE</th></tr> <tr><td>Nickel Barrier</td></tr> </table>	CONDUCTOR TYPE	Nickel Barrier	<table border="1"> <tr><th>CURVE</th></tr> <tr><td>01</td></tr> <tr><td>02</td></tr> <tr><td>03</td></tr> <tr><td>04</td></tr> <tr><td>05</td></tr> <tr><td>06</td></tr> <tr><td>10</td></tr> <tr><td>11</td></tr> <tr><td>17</td></tr> </table>	CURVE	01	02	03	04	05	06	10	11	17	<table border="1"> <tr><th>CHARACTERISTIC</th></tr> <tr><td>N</td></tr> </table>	CHARACTERISTIC	N	<table border="1"> <tr><th>RESISTANCE VALUE</th></tr> <tr><td>1002 = 10K</td></tr> </table>	RESISTANCE VALUE	1002 = 10K	<table border="1"> <tr><th>TOLERANCE CODE</th></tr> <tr><td>F = ± 1 %</td></tr> <tr><td>J = ± 5 %</td></tr> <tr><td>K = ± 10 %</td></tr> </table>	TOLERANCE CODE	F = ± 1 %	J = ± 5 %	K = ± 10 %	<table border="1"> <tr><th>PACKAGING</th></tr> <tr><td>F = Lead (Pb)-free, Bulk</td></tr> <tr><td>E = Lead (Pb)-free, T/R (Full)</td></tr> <tr><td>P = Tin/Lead, Bulk</td></tr> <tr><td>R = Tin/Lead T/R (Full)</td></tr> </table>	PACKAGING	F = Lead (Pb)-free, Bulk	E = Lead (Pb)-free, T/R (Full)	P = Tin/Lead, Bulk	R = Tin/Lead T/R (Full)
GLOBAL MODEL																																					
NTHS0402																																					
NTHS0603																																					
NTHS0805																																					
NTHS1206																																					
NTHS1012																																					
CONDUCTOR TYPE																																					
Nickel Barrier																																					
CURVE																																					
01																																					
02																																					
03																																					
04																																					
05																																					
06																																					
10																																					
11																																					
17																																					
CHARACTERISTIC																																					
N																																					
RESISTANCE VALUE																																					
1002 = 10K																																					
TOLERANCE CODE																																					
F = ± 1 %																																					
J = ± 5 %																																					
K = ± 10 %																																					
PACKAGING																																					
F = Lead (Pb)-free, Bulk																																					
E = Lead (Pb)-free, T/R (Full)																																					
P = Tin/Lead, Bulk																																					
R = Tin/Lead T/R (Full)																																					
Historical Part Number example: NTHS1206N02N1002JR (will continue to be accepted)																																					
<table border="1"> <tr><td>NTHS1206</td></tr> <tr><th>HISTORICAL MODEL</th></tr> </table>	NTHS1206	HISTORICAL MODEL	<table border="1"> <tr><td>N</td></tr> <tr><th>CONDUCTOR TYPE</th></tr> </table>	N	CONDUCTOR TYPE	<table border="1"> <tr><td>02</td></tr> <tr><th>CURVE</th></tr> </table>	02	CURVE	<table border="1"> <tr><td>N</td></tr> <tr><th>CHARACTERISTIC</th></tr> </table>	N	CHARACTERISTIC	<table border="1"> <tr><td>1002</td></tr> <tr><th>RESISTANCE VALUE</th></tr> </table>	1002	RESISTANCE VALUE	<table border="1"> <tr><td>J</td></tr> <tr><th>TOLERANCE</th></tr> </table>	J	TOLERANCE	<table border="1"> <tr><td>R</td></tr> <tr><th>PACKAGING</th></tr> </table>	R	PACKAGING																	
NTHS1206																																					
HISTORICAL MODEL																																					
N																																					
CONDUCTOR TYPE																																					
02																																					
CURVE																																					
N																																					
CHARACTERISTIC																																					
1002																																					
RESISTANCE VALUE																																					
J																																					
TOLERANCE																																					
R																																					
PACKAGING																																					

DIMENSIONS in inches [millimeters]



PART NUMBER	L	W	BW
NTHS-0402	0.040 ± 0.004 [1.016 ± 0.102]	0.022 ± 0.006 [0.5 ± 0.051]	0.010 ± 0.004 [0.25 ± 0.102]
NTHS-0603	0.063 ± 0.008 [1.6 ± 0.20]	0.031 ± 0.008 [0.80 ± 0.20]	0.010 ± 0.006 [0.25 ± 0.15]
NTHS-0805	0.079 ± 0.008 [2.00 ± 0.20]	0.049 ± 0.008 [1.25 ± 0.20]	0.012 ± 0.006 [0.30 ± 0.15]
NTHS-1206	0.126 ± 0.008 [3.20 ± 0.20]	0.063 ± 0.008 [1.60 ± 0.20]	0.018 ± 0.008 [0.46 ± 0.20]
NTHS-1012	0.098 ± 0.008 [2.50 ± 0.20]	0.126 ± 0.008 [3.20 ± 0.20]	0.018 ± 0.008 [0.46 ± 0.20]

TYPICAL PRODUCT RTC CHARACTERISTICS									
CURVE	1	2	3	4	5	6	10	11	17
NTC%/°C at + 25 °C	- 4.4	- 3.83	- 3.5	- 4.68	- 4.3	- 3.6	- 3.9	- 4.0	- 4.54
Beta + 25 °C/+ 75 °C	3964	3477	3181	4247	3890	3254	3500	3700	4064

Beta Tolerance is ± 3 %



Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.