


DO 7 DO 41 DO 29 DO 27
(CB 26) (CB 101) (CB 126) (CB 197)



CB 170 CB 169



DO 4
(CB 33)

Silicon rectifier diodes – Normal series

Diodes de redressement au silicium – Séries normales

Type	Case Boîtier	V _{RRM} (V)	T _{oper} (°C) max	I _O (A)	I _{FSM} (A) t _p 10 ms	V _F / I _F (V) (A) 25 °C max	I _R / V _{RRM} (μA) 25 °C max	DRT 76 Page
1N 645	DO 7	225	150	0,4 T _{amb} 25 °C	3(1)	1 0,4	0,2	93
1N 646	DO 7	300	150	0,4 T _{amb} 25 °C	3(1)	1 0,4	0,2	93
1N 647	DO 7	400	150	0,4 T _{amb} 25 °C	3(1)	1 0,4	0,2	93
1N 648	DO 7	500	150	0,4 T _{amb} 25 °C	3(1)	1 0,4	0,2	93
1N 649	DO 7	600	150	0,4 T _{amb} 25 °C	3(1)	1 0,4	0,2	93
1N 4001	DO 41	50	175	1 T _{amb} 75 °C	30	1,1 1	5	105
1N 4002	DO 41	100	175	1 T _{amb} 75 °C	30	1,1 1	5	105
1N 4003	DO 41	200	175	1 T _{amb} 75 °C	30	1,1 1	5	105
1N 4004	DO 41	400	175	1 T _{amb} 75 °C	30	1,1 1	5	105
1N 4005	DO 41	600	175	1 T _{amb} 75 °C	30	1,1 1	5	105
1N 4006	DO 41	800	175	1 T _{amb} 75 °C	30	1,1 1	5	117
1N 4007	DO 41	1000	175	1 T _{amb} 75 °C	30	1,1 1	5	117
ESM 100	DO 29	100	175	1 T _{amb} 50 °C	50	1 1	10	117
1N 4383	DO 29	200	175	1 T _{amb} 50 °C	50	1 1	10	117
1N 4384	DO 29	400	175	1 T _{amb} 50 °C	50	1 1	10	117
1N 4385	DO 29	600	175	1 T _{amb} 50 °C	50	1 1	10	117
1N 4585	DO 29	800	175	1 T _{amb} 50 °C	50	1 1	10	117
1N 4586	DO 29	1000	175	1 T _{amb} 50 °C	50	1 1	10	117
1N 5059	CB 170	200	175	1 T _{amb} 75 °C	50	1,2 1	5	109
1N 5060	CB 170	400	175	1 T _{amb} 75 °C	50	1,2 1	5	109
1N 5061	CB 170	600	175	1 T _{amb} 75 °C	50	1,2 1	5	109
1N 5062	CB 170	800	175	1 T _{amb} 75 °C	50	1,2 1	5	109
1N 5624	CB 169	200	175	3 T _{amb} 70 °C	125	1 3	5	113
1N 5625	CB 169	400	175	3 T _{amb} 70 °C	125	1 3	5	113
1N 5626	CB 169	600	175	3 T _{amb} 70 °C	125	1 3	5	113
1N 5627	CB 169	800	175	3 T _{amb} 70 °C	125	1 3	5	113
BY 251	DO 27 pl.	200	150	3 T _{amb} 50 °C	100	1,1 3	20	#
BY 252	DO 27 pl.	400	150	3 T _{amb} 50 °C	100	1,1 3	20	#
BY 253	DO 27 pl.	600	150	3 T _{amb} 50 °C	100	1,1 3	20	#
BY 254	DO 27 pl.	800	150	3 T _{amb} 50 °C	100	1,1 3	20	#
BY 255	DO 27 pl.	1300	150	3 T _{amb} 50 °C	100	1,1 3	20	#
1N 1581	DO 4	50	175	3 T _{case} 150 °C	40	1,5(2) 3	5000(2)	101
1N 1582	DO 4	100	175	3 T _{case} 150 °C	40	1,5(2) 3	5000(2)	101
1N 1583	DO 4	200	175	3 T _{case} 150 °C	40	1,5(2) 3	5000(2)	101
1N 1584	DO 4	300	175	3 T _{case} 150 °C	40	1,5(2) 3	5000(2)	101
1N 1585	DO 4	400	175	3 T _{case} 150 °C	40	1,5(2) 3	5000(2)	101
1N 1586	DO 4	500	175	3 T _{case} 150 °C	40	1,5(2) 3	5000(2)	101

(1) t_p 1ms (2) T_{case} 150 °C # To be published later
Sera publiée ultérieurement