

UF4001 THRU UF4007


CURRENT 1.0 Ampere
VOLTAGE 50 to 1000 Volts

Features

- Plastic package has Underwriters Laboratory Flammability Classification 94V-0
- Low forward voltage drop
- High current capability
- High reliability
- Low power loss, high efficiency
- High surge current capability
- High speed switching
- Low leakage

Mechanical Data

- Case : JEDEC DO-41 molded plastic body
- Epoxy : UL94V-0 rate flame retardant
- Lead : Plated axial lead solderable per MIL-STD-750, method 2026
- Polarity : Color band denotes cathode end
- Mounting Position : Any
- Weight : 0.012 ounce, 0.33 gram



Maximum Ratings And Electrical Characteristics

(Ratings at 25 °C ambient temperature unless otherwise specified, Single phase, half wave 60Hz, resistive or inductive load. For capacitive load, derate by 20%)

	Symbols	UF 4001	UF 4002	UF 4003	UF 4004	UF 4005	UF 4006	UF 4007	Units
Maximum recurrent peak reverse voltage	V_{RRM}	50	100	200	400	600	800	1000	Volts
Maximum RMS voltage	V_{RMS}	35	70	140	280	420	560	700	Volts
Maximum DC blocking voltage	V_{DC}	50	100	200	400	600	800	1000	Volts
Maximum average forward rectified current 0.375"(9.5mm) lead length at $T_A=50^\circ C$	$I_{(AV)}$	1.0							Amp
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load (JEDEC method)	I_{FSM}	30.0							Amps
Maximum instantaneous forward voltage at 1.0A	V_F	1.0		1.3		1.7			Volts
Maximum DC reverse current at rated DC blocking voltage	I_R	5.0							μA
Maximum full load reverse current full cycle average. 0.375"(9.5mm) lead length at $T_L=55^\circ C$		100							
Maximum reverse recovery time (Note 1)	T_{rr}	50				75			ns
Typical junction capacitance (Note 2)	C_J	20				10			pF
Operating junction and storage temperature range	T_J T_{STG}	-65 to +150							$^\circ C$

Notes:

- (1) Test conditions: $I_F=0.5A$, $I_R=1.0A$, $I_{rr}=0.25A$.
- (2) Measured at 1MHz and applied reverse voltage of 4.0 Volts.