

2N1202 - 2N1291

TYPE	MATERIAL	POLARITY	REPLACE- MENT	PAGE NUMBER	USE	MAXIMUM RATINGS					ELECTRICAL CHARACTERISTICS														
						P _D @ 25°C	Ref Point	T _J °C	V _{CB} (volts)	V _{CE} — (volts)	Subscript	h _{FE} @ I _C		V _{CE(SAT)} @ I _C		h _{FE} —	Subscript	f _T —		Subscript					
						(min)	(max)	Units	(volts)	Units	Units	Units	Units	Units	Units	Units	Units								
2N1202	G	P	2N2145	7-78	PMS	34W	J	95	80	60	0	40	120	500M	0.3	500M							200K	T	
2N1203	G	P	2N2146	7-78	PMS	34W	J	95	120	70	0	25	75	2.0A	0.6	2.0A							200K	T	
2N1204	G	P		8-92	HSS	200M	A	100	20	15	0	15		400M	0.5	200M							220M	T	
2N1204A	G	P		8-92	HSS	200M	A	100	20	15	0	25		200M	0.4	200M							220M	T	
2N1206	G	P			RFA	3.0M	A	200	60	60	0	20	80										10M	T	
2N1207	G	P			RFA	3.0M	A	200	125	125	0	20	80										10M	T	
2N1208	G	P	2N3445	7-111	LPA	45W	C	200	60	60	0	15		2.0A	5.0	2.0A							3.0M	T	
2N1209	G	P	2N3445	7-111	HFA	45W	C	200	45	45	0	20	80	2.0A	5.0	2.0A							3.0M	T	
2N1210	G	P	2N3713	7-125	HFA	30W	C	175	60	60	0	15	75	2.0A	2.0	2.0A							3.0M	T	
2N1211	G	P	2N3445	7-111	HFA	30W	C	175	80	80	0	15	75	2.0A	2.0	2.0A							3.0M	T	
2N1212	G	P	2N3445	7-111	HFA	43W	C	200	60	60	0	12	36	1.0A	5.0	1.0A							3.0M	T	
2N1213	G	P			BHS	75M	A	71	25																
2N1214	G	P			BHS	75M	A	71	25																
2N1215	G	P			BHS	75M	A	71	25																
2N1216	G	P			BHS	75M	A	71	25																
2N1217	G	P			HSA	75M	A	85	20	20	0	40	100	500*									6.0M	B	
2N1218	G	P			LPA	20W	C	90	45	45	0	30	120	1.0A	1.0	1.0A							7.0K	B	
2N1219	G	P			AFA	0.25W	A	175	30	25	0	18		5.0M									5.0M	B	
2N1220	G	P			AFA	0.25W	A	175	30	25	0	9.0		5.0M									5.0M	B	
2N1221	G	P			AFA	0.25W	A	175	30	25	0												2.0M	B	
2N1222	G	P			AFA	0.25W	A	175	30	25	0												2.0M	B	
2N1223	G	P			AFA	0.25W	A	175	40	40	0												2.0M	B	
2N1224	G	P			BHS	120M	A	85	40	40															
2N1225	G	P			RFC	120M	A	85	40	40															
2N1226	G	P	2N3611	7-118	RFC	120M	A	85	60																
2N1227	G	P			LPA	50W	C	95	35	20	0	50	350	0.5A	0.8	1.5A							3.0K	E	
2N1228	G	P			MSA	0.4W	A	160	15	15	0				0.2	10M							14	E	
2N1229	G	P			MSA	0.4W	A	160	15	15	0				0.2	10M							28	E	
2N1230	G	P			MSA	0.4W	A	160	35	35	0				0.2	10M							14	E	
2N1231	G	P			MSA	0.4W	A	160	35	35	0				0.2	10M							28	E	
2N1232	G	P			MSA	0.4W	A	160	60	60	0				0.2	10M							14	E	
2N1233	G	P			MSA	0.4W	A	160	60	60	0				0.2	10M							28	E	
2N1234	G	P			MSA	0.4W	A	160	60	60	0				0.2	10M							14	E	
2N1235	G	P			LPA	85W	C	200	120	120	0	12	60	1.0A	5.0	1.0A							50K	E	
2N1238	G	P			MSA	1.0W	A	160	15	15	0				0.2	10M							14	E	
2N1239	G	P			MSA	1.0W	A	160	15	15	0				0.2	10M							28	E	
2N1240	G	P			MSA	1.0W	A	160	35	35	0				0.2	10M							14	E	
2N1241	G	P			MSA	1.0W	A	160	35	35	0				0.2	10M							28	E	
2N1242	G	P			MSA	1.0W	A	160	60	60	0				0.2	10M							14	E	
2N1243	G	P			MSA	1.0W	A	160	60	60	0				0.2	10M							28	E	
2N1244	G	P			MSA	1.0W	A	160	110	110	0				0.2	10M							14	E	
2N1245	G	P			LPA	20W	C	85	30	25	R	50		0.5A											
2N1246	G	P			LPA	20W	C	85	30	25	R	50		0.5A											
2N1247	G	P			AFA	30M	A	150	6.0	6.0	0	15		5.0*											
2N1248	G	P			AFA	30M	A	150	6.0	6.0	0	15		20*											
2N1249	G	P			AFA	30M	A	150	6.0	6.0	0	20		30*											
2N1250	G	P	2N3713	7-125	LPA	85W	C	200	60	60	0	15		2.0A	5.0	2.0A									
2N1251	G	P			AFA	150M	A	85	20	15	R				0.5	100M							70	E	
2N1252	G	P	2N2537	8-151	MSS	600M	A	175	30	20	R	15	45	150M	1.5	150M								40M	T
2N1252A	G	P	2N2537	8-151	MSA	800M	A	300	60	30	R	15	45	150M	1.5	150M								40M	T
2N1253	G	P	2N2537	8-151	MSS	600M	A	175	30	20	R	30	90	150M	1.5	150M								50M	T
2N1253A	G	P	2N2537	8-151	MSA	800M	A	300	60	30	R	30	90	150M	1.5	150M								50M	T
2N1254	G	P			HSS	275M	A	200	30	30	0	25	50	10M	0.3	10M								30M	T
2N1255	G	P			HSS	275M	A	200	30	30	0	40	80	10M	0.3	10M								50M	T
2N1256	G	P			HSS	275M	A	200	40	40	0	25	50	10M	0.3	10M								30M	T
2N1257	G	P			HSS	275M	A	200	40	40	0	40	80	10M	0.3	10M								50M	T
2N1258	G	P			HSS	275M	A	200	30	30	0	75	150	10M	0.6	10M								50M	T
2N1259	G	P			HSS	275M	A	200	50	50	0	25	100	10M	0.3	10M								40M	T
2N1260	G	P			LPA	85W	C	200	120	120	R	12	60	1.0A	10	1.0A								50K	E
2N1261	G	P	2N1531	7-60	PMS	34W	J	95	80	45	0	20	50	2.0A	0.6	2.0A								200K	T
2N1262	G	P	2N1531	7-60	PMS	34W	J	95	80	45	0	30	75	2.0A	0.6	2.0A								200K	T
2N1263	G	P	2N3617	7-121	PMS	34W	J	95	80	45	0	45	113	2.0A	0.6	2.0A								200K	T
2N1264	G	P	2N1191	6-30	RFC	50M	A	75	20	20	0														
2N1265	G	P	2N1192	6-30	RFC	50M	A	85	12	10	R				0.5	100M								600K	B
2N1266	G	P	2N1191	6-30	RFC	80M	A	85	10																
2N1267	G	P			RFA	150M	A	150	20	15	0	4.0	16	1.5M	</										